



Heat Shrink Specification Chart (By Size)

Component Supply Part Number	Material	Shrink Ratio	Expanded ID (IN)	Recovered ID (IN)	Wall Thickness (IN)	Length (IN)
PBST2-014-002C	Pebax	2:1	0.0140	0.0070	0.0020	60
IPST2-016C	Polyolefin	2:1	0.0160	0.0100	0.0020	60
IPST2-025C	Polyolefin	2:1	0.0200	0.0100	0.0050	60
SMT-24	FEP	1.3:1	0.0310	0.0270	0.0080	48
SM2TSW-30	PTFE	2:1	0.0340	0.0150	0.0090	48
SM2T-30	PTFE	2:1	0.0340	0.0150	0.006	48
IPST2-034C	Polyolefin	2:1	0.0340	0.0200	0.0050	60
SMT-22	FEP	1.3:1	0.0360	0.0320	0.0080	48
PBST2-040-40-004C	Pebax	2:1	0.0360	0.0200	0.0040	60
SM2TSW-28	PTFE	2:1	0.0380	0.0180	0.0090	48
SM2T-28	PTFE	2:1	0.0380	0.0180	0.006	48
SMT-20	FEP	1.3:1	0.0450	0.0390	0.0080	48
SM2TSW-26	PTFE	2:1	0.0460	0.0220	0.0100	48
SM2T-26	PTFE	2:1	0.0460	0.0220	0.006	48
SM2TSW-24	PTFE	2:1	0.0500	0.0270	0.0120	48
SM2TTW-24	PTFE	2:1	0.0500	0.0270	0.0100	48
SM2T-24	PTFE	2:1	0.0500	0.0270	0.006	48
IPST2-055C	Polyolefin	2:1	0.0500	0.0350	0.0020	60
SM2TSW-22	PTFE	2:1	0.0550	0.0320	0.0120	48
SM2TTW-22	PTFE	2:1	0.0550	0.0320	0.0100	48
SM2T-22	PTFE	2:1	0.0550	0.0320	0.006	48
SM2TSW-20	PTFE	2:1	0.0600	0.0390	0.0160	48
SM2TTW-20	PTFE	2:1	0.0600	0.0390	0.0100	48
SM2T-20	PTFE	2:1	0.0600	0.0390	0.006	48
SMT-18	FEP	1.3:1	0.0600	0.0490	0.0080	48
PBST2-060-003C	Pebax	2:1	0.0600	0.0350	0.0030	60
PBST2-060-010C	Pebax	2:1	0.0600	0.0350	0.0100	60
PBST2-060-40-003C	Pebax	2:1	0.0600	0.0350	0.0030	60
PBST2-060-40-010C	Pebax	2:1	0.0600	0.0350	0.0100	60
SM2TSW-19	PTFE	2:1	0.0650	0.0430	0.0160	48
SM2TTW-19	PTFE	2:1	0.0650	0.0430	0.0100	48
SM2T-19	PTFE	2:1	0.0650	0.0430	0.006	48
IPST2-070C	Polyolefin	2:1	0.0660	0.0350	0.0030	60
HSF16-0440	FEP	1.6:1	0.0680	0.0440	0.0080	72
SMT-16	FEP	1.3:1	0.0750	0.0610	0.0090	48

Component Supply Part Number	Material	Shrink Ratio	Expanded ID (IN)	Recovered ID (IN)	Wall Thickness (IN)	Length (IN)
SM2TSW-18	PTFE	2:1	0.0760	0.0490	0.0160	48
SM2TTW-18	PTFE	2:1	0.0760	0.4900	0.0100	48
SM2T-18	PTFE	2:1	0.0760	0.0490	0.006	48
SM4T-0078	PTFE	4:1	0.0780	0.0250	0.0090	48
SM2TSW-17	PTFE	2:1	0.0850	0.0540	0.0160	48
SM2TTW-17	PTFE	2:1	0.0850	0.0540	0.0100	48
SM2T-17	PTFE	2:1	0.0850	0.0540	0.006	48
SMT-14	FEP	1.3:1	0.0920	0.0720	0.0090	48
SM2TSW-16	PTFE	2:1	0.0930	0.0610	0.0160	48
SM2TTW-16	PTFE	2:1	0.0930	0.0610	0.0100	48
SM2T-16	PTFE	2:1	0.0930	0.0610	0.006	48
SM16T-0093	FEP	1.6:1	0.0930	0.0560	0.0080	48
SM2TSW-15	PTFE	2:1	0.1100	0.0670	0.0160	48
SM2TTW-15	PTFE	2:1	0.1100	0.0670	0.0100	48
SM2T-15	PTFE	2:1	0.1100	0.0670	0.006	48
HSF16-0680	FEP	1.6:1	0.1100	0.0680	0.0100	72
SMT-12	FEP	1.3:1	0.1150	0.0890	0.0090	48
SM2TSW-14	PTFE	2:1	0.1200	0.0720	0.0160	48
SM2TTW-14	PTFE	2:1	0.1200	0.0720	0.0100	48
SM2T-14	PTFE	2:1	0.1200	0.0720	0.008	48
SM4T-0125	PTFE	4:1	0.1250	0.0370	0.0120	48
SM16T-0125	FEP	1.6:1	0.1250	0.0750	0.0100	48
PBST2-140-40-006C	Pebax	2:1	0.1300	0.0750	0.0060	60
HSF16-0850	FEP	1.6:1	0.1360	0.0850	0.0100	72
SM2TSW-13	PTFE	2:1	0.1400	0.0800	0.0160	48
SM2TTW-13	PTFE	2:1	0.1400	0.0800	0.0100	48
SM2T-13	PTFE	2:1	0.1400	0.0800	0.008	48
SMT-10	FEP	1.3:1	0.1410	0.1120	0.0100	48
SM2TSW-12	PTFE	2:1	0.1500	0.0890	0.0160	48
SM2TTW-12	PTFE	2:1	0.1500	0.0890	0.0100	48
SM2T-12	PTFE	2:1	0.1500	0.0890	0.008	48
SMT-09	FEP	1.3:1	0.1580	0.1240	0.0100	48
SM2TSW-11	PTFE	2:1	0.1700	0.1010	0.0160	48
SM2TTW-11	PTFE	2:1	0.1700	0.1010	0.0100	48
SM2T-11	PTFE	2:1	0.1700	0.1010	0.008	48
HSF16-1090	FEP	1.6:1	0.1750	0.1090	0.0100	72
SMT-08	FEP	1.3:1	0.1800	0.1410	0.0100	48
SM4T-0187	PTFE	4:1	0.1870	0.0500	0.0120	48
SM16T-0188	FEP	1.6:1	0.1880	0.1150	0.0100	48
HSF16-1180	FEP	1.6:1	0.1880	0.1180	0.0100	72
SM2TSW-10	PTFE	2:1	0.1910	0.1120	0.0160	48

Component Supply Part Number	Material	Shrink Ratio	Expanded ID (IN)	Recovered ID (IN)	Wall Thickness (IN)	Length (IN)
SM2TTW-10	PTFE	2:1	0.1910	0.1120	0.0100	48
SM2T-10	PTFE	2:1	0.1910	0.1120	0.008	48
SMT-07	FEP	1.3:1	0.1970	0.1580	0.0110	48
SM2TSW-09	PTFE	2:1	0.2050	0.1240	0.0200	48
SM2TTW-09	PTFE	2:1	0.2050	0.1240	0.0150	48
SM2T-09	PTFE	2:1	0.2050	0.1240	0.008	48
SMT-06	FEP	1.3:1	0.2250	0.1780	0.0110	48
SM2TSW-08	PTFE	2:1	0.2400	0.1410	0.0200	48
SM2TTW-06	PTFE	2:1	0.2400	0.1780	0.0150	48
SM2TTW-08	PTFE	2:1	0.2400	0.1410	0.0150	48
SM2T-08	PTFE	2:1	0.2400	0.1410	0.008	48
HSF16-1530	FEP	1.6:1	0.2460	0.1530	0.0100	72
SMT-05	FEP	1.3:1	0.2480	0.1980	0.0110	48
SM4T-0250	PTFE	4:1	0.2500	0.0630	0.0120	48
SM16T-0250	FEP	1.6:1	0.2500	0.1500	0.0100	48
SM2TSW-07	PTFE	2:1	0.2700	0.1580	0.0200	48
SM2TTW-07	PTFE	2:1	0.2700	0.1580	0.0150	48
SM2T-07	PTFE	2:1	0.2700	0.1580	0.008	48
SMT-04	FEP	1.3:1	0.2900	0.2240	0.0110	48
SM2TSW-06	PTFE	2:1	0.3020	0.1780	0.0200	48
SM2T-06	PTFE	2:1	0.3020	0.1780	0.010	48
SMT-03	FEP	1.3:1	0.3100	0.2490	0.0110	48
SM4T-0312	PTFE	4:1	0.3120	0.0780	0.0120	48
SM2TSW-05	PTFE	2:1	0.3200	0.1980	0.0200	48
SM2TTW-05	PTFE	2:1	0.3200	0.1980	0.0150	48
SM2T-05	PTFE	2:1	0.3200	0.1980	0.010	48
SMT-02	FEP	1.3:1	0.3650	0.2780	0.0120	48
SM2TSW-04	PTFE	2:1	0.3700	0.2240	0.0200	48
SM2TTW-04	PTFE	2:1	0.3700	0.2240	0.0150	48
SM2T-04	PTFE	2:1	0.3700	0.2240	0.010	48
SM4T-0375	PTFE	4:1	0.3750	0.0960	0.0120	48
SM16T-0375	FEP	1.6:1	0.3750	0.2250	0.0120	48
SM2TSW-03	PTFE	2:1	0.3900	0.2490	0.0200	48
SM2TTW-03	PTFE	2:1	0.3900	0.2490	0.0150	48
SM2T-03	PTFE	2:1	0.3900	0.2490	0.010	48
SMT-01	FEP	1.3:1	0.4000	0.3110	0.0120	48
SM2TSW-02	PTFE	2:1	0.4300	0.2780	0.0200	48
SM2TTW-02	PTFE	2:1	0.4300	0.2780	0.0150	48
SM2T-02	PTFE	2:1	0.4300	0.2780	0.010	48
SM4T-0438	PTFE	4:1	0.4380	0.1120	0.0120	48
SMT-00	FEP	1.3:1	0.4400	0.3470	0.0120	48

Component Supply Part Number	Material	Shrink Ratio	Expanded ID (IN)	Recovered ID (IN)	Wall Thickness (IN)	Length (IN)
SM2TSW-01	PTFE	2:1	0.4500	0.3110	0.0200	48
SM2TTW-01	PTFE	2:1	0.4500	0.3110	0.0150	48
SM2T-01	PTFE	2:1	0.4500	0.3110	0.010	48
SM2TSW-00	PTFE	2:1	0.4700	0.3470	0.0200	48
SM2TTW-00	PTFE	2:1	0.4700	0.3470	0.0150	48
SM2T-00	PTFE	2:1	0.4700	0.3470	0.012	48
SM4T-0500	PTFE	4:1	0.5000	0.1440	0.0150	48
SM16T-0500	FEP	1.6:1	0.5000	0.3000	0.0150	48
SM4T-0562	PTFE	4:1	0.5620	0.1550	0.0150	48
SM4T-0625	PTFE	4:1	0.6250	0.1780	0.0150	48
SM4T-0687	PTFE	4:1	0.6870	0.1980	0.0150	48
SM4T-0750	PTFE	4:1	0.7500	0.2240	0.0150	48
SM16T-0750	FEP	1.6:1	0.7500	0.4500	0.0200	48
SM16T-1000	FEP	1.6:1	1.0000	0.6000	0.0250	48
SM16T-1500	FEP	1.6:1	1.5000	0.9000	0.0300	48
SM16T-2000	FEP	1.6:1	2.0000	1.2000	0.0300	48