



Polyester Mesh Specification Chart

Component Supply Part Number	Mesh Opening (Microns)	Open Area %	Thread Count (n/Inch)	Thread Diameter (Microns)	Mesh Thickness (Microns)
U-CMY-10	10	3	317x571	34x40	80
U-CMY-1010	1010	44	69	120	950
U-CMY-105	105	33	140	70	114
U-CMY-120	120	41	140	60	105
U-CMY-150	150	43	109	80	138
U-CMY-160	160	40	102	90	153
U-CMY-18	18	13	508	38	60
U-CMY-1800	1800	64	11	500	970
U-CMY-200	200	43	81	100	170
U-CMY-25	25	20	457	27	52
U-CMY-250	250	44	69	120	222
U-CMY-30	30	24	419	31	60
U-CMY-330	330	46	53	160	300
U-CMY-41	41	28	330	34	60
U-CMY-500	500	48	36	220	400
U-CMY-53	53	40	305	31	48
U-CMY-530	530	50	34	220	410
U-CMY-600	600	51	30	240	450
U-CMY-70	70	28	196	55	90
U-CMY-700	700	52	27	260	478
U-CMY-810	810	55	24	280	533
U-CMYBK-250	250	37	61	160	274
U-CMYBK-53	53	40	305	31	48